



**LEGEND**

- (K) Full Depth Bituminous Pavement \*  
60 kg/m<sup>2</sup> QC/QA HMA Surface 9.5mm, Mainline, on  
150 kg/m<sup>2</sup> QC/QA HMA Intermediate 19.0mm, Mainline, on  
270 kg/m<sup>2</sup> QC/QA HMA Base 25.0mm, Mainline, on  
248 kg/m<sup>2</sup> HMA Base C25.0mm, Mainline  
270 kg/m<sup>2</sup> QC/QA HMA Base 25.0mm, Mainline
  - Where (M) Bituminous Milling
  - (R) Bituminous Resurface \*  
60 kg/m<sup>2</sup> QC/QA HMA Surface 9.5mm, Mainline, on  
150 kg/m<sup>2</sup> QC/QA HMA Intermediate 19.0mm, Mainline
  - (R<sub>1</sub>) Bituminous Resurface \*  
60 kg/m<sup>2</sup> QC/QA HMA Surface 9.5mm, Mainline
  - (W) Bituminous Widening \*  
270 kg/m<sup>2</sup> QC/QA HMA Base 25.0mm, Mainline, on  
248 kg/m<sup>2</sup> HMA Base C25.0mm, Mainline  
270 kg/m<sup>2</sup> QC/QA HMA Base 25.0mm, Mainline
  - (15) Curb and Gutter, Concrete, Modified
- \* Asphalt Binder PG70-22

DIMENSIONS IN METERS UNLESS OTHERWISE NOTED.

846401 (252) (20-1) (08-20-87)						RECOMMENDED FOR APPROVAL <i>Paul D. Barry 9/1/87</i> DESIGN ENGINEER DATE	<b>INDIANA DEPARTMENT OF TRANSPORTATION</b>  <b>OAK GROVE ROAD</b> <b>TYPICAL CROSS SECTIONS</b>	HORIZONTAL SCALE <i>none</i>	BRIDGE FILE
						DESIGNED: <i>ATW</i> DRAWN: <i>CEB</i>		VERTICAL SCALE <i>none</i>	DESIGNATION
						CHECKED: <i>GLR</i> CHECKED: <i>GLR</i>		SURVEY BOOK	SHEETS 4 of 90
								CONTRACT	PROJECT VC97-09-01